



REDIFRAME®



REDIFLEX®

*The Original PRE-FINISHED
Steel Door Frames*

16 GAUGE REDIFRAME® AND REDIFLEX®

Architects and builders have trusted Dunbarton to produce quality steel frames for nearly fifty years. Whether crafting door frames for residential buildings or producing frames that can take the impact from heavy commercial use, Dunbarton's steel frames, RediFrame®, and RediFlex® have set a high standard for performance and quality!

REDIFRAME® is a pre-finished, fixed-throat steel door frame suitable for interior and exterior applications where a strong steel door frame is needed.

REDIFLEX® is a steel door frame featuring an adjustable throat, proven valuable in situations with varying wall sizes, for single and paired openings, and is ideal for pre-hanging.

RediFrame® and RediFlex® are constructed from 16-gauge steel, providing strength and durability, making them perfect for new construction, remodeling projects, residential buildings, or commercial use.

Experience the exceptional performance and unmatched quality of 16-gauge Rediframe® and Rediflex®. Setting the standard in the industry, they are the smart choice for your projects!

- Frames are pre-finished, so installation occurs **AFTER** the wall is finished.
- Available with **28 different electric strike preps, offset ASA preps, concealed closure, and overhead stops. Along with EPT, flush bolt roller latches, electric hinge, and light switch preps.**
- Frames sleeve the wall, but it anchors to the wall using at least 30 fasteners.
- Frames carry a Certification of Level A 1,000,000 cycles (ANSI 250.5-1994).
- Warnock Hersey standard in both neutral (UL 10B) and positive (UL 10C) pressure fire ratings.

*Test results available upon request.



Scan to go directly to
REDIFRAME | REDIFLEX
product webpage!

16 Gauge Standard Options:

- A-40 galvanealed only
- 1-3/4" and 1-3/8" doors
- 4" to 12-1/4" (1-1/4" adjustments)
- Standard double rabbet, single rabbet and cased opening jamb profiles
- 5/8" stop height
- Demountable without damage to the finished wall, door or frame
- Standard frame prep wood casing (other supplier)
- Standard steel, S56 Colonial, and aluminum casing available and supplied with field installed clips
- Hinge options include: welded 3-1/2", 4", 4"x5/8"R, 4-1/2" STD, 4-1/2" HVY WT, and 5" HVY WT
- Strike options include: welded 2-3/4" STD T-Strike, Standard 4-7/8" ANSI, 2-1/4" Full Lip, 2-3/4" Deadbolt and 2-1/4" Deadbolt
- Mylar 90 minute neutral and positive pressure fire label; wood or steel stud
- Available in kerf and non-kerf

Other Options:

- Special hinge and strike location
- Non-standard wall size



**DUNBARTON
CORPORATION**
Your Complete Opening Solution

1101 Technology Drive | Dothan, Alabama 36303
800.633.7553 | 334.794.9184 fax
dunbarton.com | sales@dunbarton.com



Proudly made
in America