



REDIFLEX-TH™

The *Original* PRE-FINISHED Steel Door Frames

Gasket wraps
around frame.



NEW! **REDIFLEX-TH™** **THERMALLY BROKEN REDIFLEX FRAME**

**PROTECTION FROM EXTREME
TEMPERATURES**

Standard **REDIFLEX-TH™**
Thermally Broken Flex Frame
Options:

MATERIAL: 16 gauge and 18 gauge cold rolled steel (standard) or 16 gauge and 18 gauge A40 Galvalume

DOOR THICKNESS: For use with 1-3/8" or 1-3/4" thickness doors (steel or wood)

WALL SIZE: 4" to 12-1/4"

STOP HEIGHT: 5/8"

HINGE REINFORCEMENTS: Prepared for standard hinges

FINISHING: White or grey primed, standard colors, or custom colors available

STRIKE PREP: T-Strike, ASA prep, deadbolt

***Combined, REDIFLEX-TH, a high efficiency door and threshold provide greater than 50% improvement in U-Factor and energy efficiency compared to standard door systems.**



REDIFLEX-TH™
Keeps extreme weather out with a strong-as-the-wall design and easy onsite assembly!

Keep your home or office comfortable in any weather with the newest addition to the **REDIFLEX** family, **REDIFLEX-TH**. Designed to block out extreme cold and heat, the **REDIFLEX-TH** delivers an easy-to-install frame ideal for exterior and interior application.


Key Features:

- Thermally broken to reduce condensation and frost on interior surfaces
- Easy-to-install gasket wraps around the entire frame
- Sturdy 16 gauge or 18 gauge steel construction
- Available as a pre-hung option
- Kerfed for weatherstripping or non-kerfed
- Available in prime, standard colors or any custom pre-painted finish



Please allow 7-8 weeks for delivery.



Scan to go directly to
REDIFRAME | REDIFLEX
product webpage!



Profile



**DUNBARTON
CORPORATION**
Your Complete Opening Solution

1101 Technology Drive | Dothan, Alabama 36303
800.633.7553 | 334.794.9184 fax
dunbarton.com | sales@dunbarton.com



Proudly made
in America