



REDIFIT™

PRE-HUNG ENTRY DOOR SYSTEM

Combine RediFlex® with factory installed weatherstripping, threshold, and door for a time-saving, pre-hung solution

- Steel or Fiberglass Doors
- RediFlex® Adjustable Frames*
- Weatherstrip
- Threshold
- Pre-Finished Standard or Custom Color

*Standard RediFlex® Options Include:

- 18 gauge (standard) and 20 gauge Cold-Rolled Steel or 16, 18, or 20 gauge A40 Galvanneal
- Special hinge or strike location
- Standard and custom colors

THE REDIFIT™ INCLUDES:


REDIFIT™ PRE-HUNG ENTRY SYSTEMS

Dunbarton Corporation proudly combines steel and fiberglass doors with its proven RediFlex® adjustable steel door frame for a time saving solution. The result is the RediFit™ system. A ready-to-install door and frame system designed to save time and money.

RediFit™ pre-hung openings offer beauty, security, and durability. They are available in non-rated and fire-rated (20-90 minutes) configurations. Our steel doors can be factory primed or pre-finished in one of our beautiful standard colors or a custom color of your choice. The fiberglass doors are offered in a smooth skin, wood grain texture, or factory finish.

CASING

Dunbarton frames and casing are designed to work together to offer the best commercial, industrial, and multi-family package. We offer casing in steel, aluminum, and S56 Colonial. However, you also have the option to use any wood trim you prefer. Additionally, all trims are available in our standard colors or custom color-matched to meet your job specifications!




Wood Casing Note: Wood casing requires a frame without casing lance. Specify frames with no lance and no casing. Wood casing can be attached to the frame face using nails or screws at the discretion of the installer. Casing profile must provide back clearance for screw heads used to install frame.

THRESHOLD


The purpose of a threshold is to close the gap between the bottom of a door and the floor. Thresholds are used with door bottoms and weatherstripping to seal the opening, preventing air, rain, and snow from entering. Dunbarton has four standard styles with two extenders for the fixed inswing, with other options available.

Frame height can be adjusted to accommodate the threshold height with a standard undercut door. Sweep height must be considered when determining the frame height, door height, and threshold height. For full threshold options, see your Dunbarton salesperson, or the Dunbarton website.



WEATHERSTRIP

Dunbarton's 90-minute fire-rated weatherstripping is available in three colors: white, brown, and beige. The easy-to-install kerf weatherstripping comes ready to install on-site or is available pre-installed. Be sure to specify weatherstripping color when ordering frames.



Color Options

White

Brown

Beige



Scan to go directly to RediFit | RediKit product webpage!



DUNBARTON CORPORATION
Your Complete Opening Solution

1101 Technology Drive | Dothan, Alabama 36303
800.633.7553 | 334.794.9184 fax
dunbarton.com | sales@dunbarton.com



Proudly made
in America